

ENOC VULCAN SVI 70

PRODUCT DESCRIPTION

ENOC VULCAN SVI 70 is a high-performance multi-grade engine oil for use in heavy duty diesel engines. It has been developed using technology suitable for use against API service classification CI-4 for mixed fleet operations where European, US and Japanese heavy and light duty trucks are used. It has excellent total base number (TBN) retention that provides durable engine protection and oil consumption control.

APPLICATIONS

- High speed diesel engines in offshore marine service (e.g. ferries, fishing boats, etc.)
- Heavy earth moving equipment used in the construction industry
- Long distance coach operations
- Mixed fleets of diesel engines
- Agricultural tractors
- Stationary power generation units using
- High speed diesel engines

PERFORMANCE STANDARDS

ENOC VULCAN SVI 70 is suitable for use against the following OEM and International specifications:

API CI-4

Always follow the equipment manufacturer's recommendations for required lubricant performance levels and oil drain intervals.

BENEFITS

ENOC VULCAN SVI 70 provides:

- Helps extend oil drain intervals
- Engine deposit control
- Reduces fleet maintenance costs
- Helps preserve full power and performance
- Excellent control of oxidation and oil thickening
- Neutralization of corrosive acids

	Technical Data*
Label Grade Description	25W-70
Kinematic Viscosity	
mm²/s @ 40°C	332.1
mm²/s @100°C	30.65
Viscosity Index	128
Flash Point, COC, °C	252
Pour Point, ^o C	-18
TBN, mg KOH/g	11.1
CCS@-10degC	11000
Product code	200058

^{*}The information prepared provides the typical properties that are considered as representative. Some variation which will not affect performance is possible

Issued by ENOC Marketing LLC, Dubai, U.A.E. Last Updated on: March 2021- MS PDS V2170321