

ENOC PROTEC 4T MAX PLUS 15W-40

ENOC PROTEC 4T MAX PLUS 15W-40 is a high performance conventional four-stroke motorcycle engine oil primarily intended for general use in all types of four-stroke motorcycles fitted with integral unit of engine, gear box & clutch assembly. It is specially formulated to give trouble free ride.

APPLICATIONS

- ◆ Recommended for 4-stroke gasoline engine of manufacturers recommending API SG, JASO MA-2 engine oil
- ◆ Four-Stroke motor cycles with integral wet clutch operation
- ◆ Air and water cooled four-stroke motor cycle engines

PERFORMANCE STANDARDS

ENOC PROTEC 4T MAX PLUS 15W-40 meets and exceeds the following OEM and International Specifications:

API SG
JASO MA2

Always follow equipment manufacturer's recommendations for required lubricant performance levels and oil drain intervals.

BENEFITS

ENOC PROTEC 4T MAX PLUS 15W-40 provides:

- ◆ Trouble free engine running due to excellent deposit control
- ◆ **Ensures protection for engine's critical components**
- ◆ Allows smooth gear shift
- ◆ Suitable for use in Catalytic converter equipped engines

Technical Data	
SAE Grade	15W-40
Kinematic Viscosity	
mm ² /s @ 40°C	104
mm ² /s @100°C	14.4
Viscosity Index	142
Flash Point, COC, °C	236
Pour Point, °C	-27
Phosphorus% Min	0.08
Product Code	220041

*The information prepared provides the typical properties that are considered as representative. Some variation which will not affect performance is possible

HEALTH AND SAFETY, ENVIRONMENT The information on this product is available in the ENOC Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information, we recommend you review the MSDS. Handled correctly there are no special precautions suggested.