

ENOC PROTEC 3W + SUPER 4T

PRODUCT DESCRIPTION

ENOC PROTEC 3W SUPER 4T is a modern high technology based 4T engine oil exceeding the latest API SG/CF performance specification. Developed to provide best protection for use in modern 3 wheelers fitted with 4 stroke air cooled motorcycle engines. It is suitable for all types of driving conditions (city, highway and harsh) and is available in 20W- 50 viscosity grade, to meet market conditions

APPLICATIONS

- 3 wheelers with Four stroke motorcycle engines where motor oils are recommended
- High performance normally aspirated 4T gasoline engines

PERFORMANCE STANDARDS

ENOC PROTEC 3W + SUPER 4T meets and exceeds the following OEM and International Specifications:

API SG/CF

Always follow equipment manufacturer's recommendations for required lubricant performance levels and oil drain intervals.

BENEFITS

ENOC PROTEC 3W + SUPER 4T provides:

- Excellent Protection to engines for load, high temperature operations as in 3-Wheelers
- Extended life using special additive technology for engine and wet clutch operation
- Helps keep engine clean for smoother operations
- Protects critical engine component
- ♦ Year-round engine protection and performance

Technical Data	
SAE Grade	20W-50
Kinematic Viscosity	
Colour	Red
Odour	Sweet Fruity odour
mm ² /s @ 40°C	170
mm ² /s @100°C	18.85
Viscosity Index	125
TBN, mg of KOH/g	8.2
Flash Point, COC, OC	241
Pour Point, °C	-24
Product Code	213053

HEALTH AND SAFETY, ENVIRONMENT The information on this product is available in the ENOC Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information, we recommend you review the MSDS. Handled correctly there are no special precautions suggested.

Printed by ENOC Marketing LLC, Dubai, U.A.E Last Updated on: October 2018- MS

PDS V2211018