

# ENOC PROTEC 3W SUPER 4T

## PRODUCT DESCRIPTION

**ENOC PROTEC 3W SUPER 4T** is a modern high technology based 4T engine oil exceeding the latest API SG performance specification. Developed to provide best protection for use in modern 3 wheelers fitted with 4 stroke air cooled motorcycle engines. It is suitable for all types of driving conditions (city, highway and harsh) and is available in 20W- 50 viscosity grade, to meet market conditions

## APPLICATIONS

- ◆ 3 wheelers with Four stroke motorcycle engines where motor oils are recommended
- ◆ High performance normally aspirated 4T gasoline engines

## PERFORMANCE STANDARDS

**ENOC PROTEC 3W SUPER 4T** meets and exceeds the following OEM and International Specifications:  
 API SG  
 JASO MA2

***Always follow equipment manufacturer's recommendations for required lubricant performance levels and oil drain intervals.***

## BENEFITS

**ENOC PROTEC 3W SUPER 4T provides:**

- ◆ Extended life using special additive technology for engine and wet clutch operation
- ◆ Smooth gear changes using special lubricant friction characteristics
- ◆ Reduced engine repairs due to cleaner engine parts

Technical Data	
<b>SAE Grade</b>	<b>20W-50</b>
Kinematic Viscosity mm <sup>2</sup> /s @ 40°C	170
mm <sup>2</sup> /s @100°C	18.85
Viscosity Index	125
TBN, mg of KOH/g	5.35
Flash Point, COC, °C	246
Pour Point, °C	-27
Product Code	213010

**HEALTH AND SAFETY, ENVIRONMENT** The information on this product is available in the ENOC Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information, we recommend you review the MSDS. Handled correctly there are no special precautions suggested.