

# ENOC PROTEC 4T SUPER

## PRODUCT DESCRIPTION

**ENOC PROTEC 4T SUPER** is a modern high technology gasoline engine oil specifically formulated for Four-Stroke motor cycles in SAE 10W- 40 viscosity grade and meeting the API SJ specification. In addition, it meets the new JASO MA2 specification which has been developed to meet the requirements for the engine and the wet clutch lubrication to provide smooth gear change operations

## APPLICATIONS

- ◆ Four-Stroke motor cycles with integral wet clutch operation
- ◆ Particularly suitable for Japanese high performance four-stroke motor cycles
- ◆ Air cooled four-stroke motor cycle engines
- ◆ Water cooled four-stroke motor cycles engines
- ◆ Portable small four-stroke gasoline engine generator sets

## PERFORMANCE STANDARDS

**PROTEC 4T SUPER** meets and exceeds the following OEM and International Specifications:

API SJ  
JASO MA2

***Always follow equipment manufacturer's recommendations for required lubricant performance levels and oil drain intervals.***

## BENEFITS

**PROTEC 4T SUPER provides:**

- ◆ Excellent engine cleanliness through advanced soot handling technology
- ◆ Mixed fleet capabilities
- ◆ Exceptional low engine wear
- ◆ Trouble free operation between long drain service intervals
- ◆ Reduced maintenance capabilities

Technical Data	
<b>SAE Grade</b>	<b>10W- 40</b>
Kinematic Viscosity mm <sup>2</sup> /s @ 40°C	94
mm <sup>2</sup> /s @100°C	14
Viscosity Index	152
Flash Point, COC, °C	236
Pour Point, °C	-36
BN No. ASTM D2896	5.5
Product Code	200024

**HEALTH AND SAFETY, ENVIRONMENT** The information on this product is available in the ENOC Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information, we recommend you review the MSDS. Handled correctly there are no special precautions suggested.