

KUWA SUPREME 9130

PRODUCT DESCRIPTION

ENOC KUWA SUPREME 9130 is a synthetic multigrade SAE 5W-30 lubricant formulated for use in modern turbocharged, Supercharged, direct injection gasoline and diesel passenger cars and light diesel trucks. KUWA SUPREME 9130 is formulated with synthetic base stock with a combination of high-performance additive components and friction modifiers. It gives long engine service performance, engine wear control, fuel efficiency, low temperature protection and exhaust emission control. Meets the requirements of ACEA European sequence A5/ B5 requirements for low friction, low viscosity lubricants for gasoline and light diesel engines.

APPLICATIONS

- All makes of passenger cars
- High performance normally aspirated and turbocharged engines
- Intended for use over extended drain intervals in high performance gasoline and light duty diesel engines.
- Light commercial vehicles

PERFORMANCE STANDARDS

KUWA SUPREME 9130 meets and exceeds the following International specifications:

API	SN*	Approved Jaguar Land Rover	STJLR.03.5003
ACEA	A5/B5	FORD	WSS-M2C913-C/D
Renault RN	700		

* Meets engine test requirements.

Always follow equipment manufacturer's recommendations for required lubricant performance level and oil drain intervals.

BENEFITS

KUWA SUPREME 9130 provides:

- The highest level of engine protection for various engine manufacturers.
- Long engine life
- Superior resistance to oil thickening
- Offers high speed, high temperature city stop/ start engine wear and corrosion protection.
- Low oil consumption and engine deposits
- Easy all year round starting

Technical Data*	
SAE Grade	5W- 30
Kinematic Viscosity mm ² /s @ 40°C	54.0
Kinematic Viscosity mm ² /s @ 100°C	9.9
Viscosity Index	168
Flash Point, COC, °C	225
Pour Point, °C	-36
Product Code	200056

The information prepared provides the typical properties that are considered as representative. Some variation which will not affect performance is possible

HEALTH AND SAFETY, ENVIRONMENT

The information on this product is available in the ENOC Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information we recommend you review the MSDS. Handled correctly there are no special precautions suggested.