

ENOC PROTEC 40

PRODUCT DESCRIPTION

ENOC PROTEC 40 is a monograde engine oil developed for gasoline and naturally aspirated diesel engines. It is ideally suited for use in cars, 2/3 wheelers and light trucks where the customers needs can be met with a cost effective lubricant using standard oil change periods. **PROTEC 40** meets the API classification SF and CD

APPLICATIONS

- ◆ Passenger cars and light commercial vehicles
- ◆ Suitable for old 2/3 wheelers
- ◆ Pumps using small gasoline and diesels engines
- ◆ Portable generator sets

PERFORMANCE STANDARDS

PROTEC HD SF meets the following International specifications:
 API SF/CD

Always follow equipment manufacturer's recommendations for required lubricant performance levels and oil drain intervals.

BENEFITS

PROTEC 40 provides:

- ◆ Good performance in gasoline and diesel engines
- ◆ Control of sludge and deposits
- ◆ Better detergent/dispersant properties
- ◆ Resist oil thickening

Technical Data*	
SAE Grade	40
Kinematic Viscosity	
mm ² /s @ 40 °C	148
mm ² /s @ 100 °C	14.5
Viscosity Index	96
Flash Point, COC, °C	248
Pour Point, °C	-15
Product Code	210060

*The information prepared provides the typical properties that are considered as representative. Some variation which will not affect performance is possible

HEALTH AND SAFETY, ENVIRONMENT

The information on this product is available in the ENOC Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information we recommend you review the MSDS. Handled correctly there are no special precautions suggested.