



ENOC PROTEC 4T SM

PRODUCT DESCRIPTION

ENOC PROTEC 4T SM is a special formulation using highly refined base oil technology suitable for modern four stroke motor cycle engines oil exceeding the performance specification **API SM**. Developed to provide maximum protection for modern four stroke motor cycle engines, including high performance engines. It is available in **SAE 20W-40** viscosity grade to provide complete lubrication solution for the motorcycle engine, clutch and gearbox requirements. Compatible for all motor cycles running on lead free gasoline.

APPLICATIONS

- ◆ Four stroke motorcycle engines
- ◆ Water and air-cooled motorcycle engines
- ◆ Latest model Japanese and European four stroke motor cycle engines

PERFORMANCE STANDARDS

PROTEC 4T SM meets and exceeds the following International specifications:

API SM
JASO MA-2

Always follow equipment manufacturer's recommendations for required lubricant performance level and oil drain intervals.

BENEFITS

PROTEC 4T SM provides:

- ◆ The highest level of engine protection for all manufacturers
- ◆ Extended engine life
- ◆ Enhanced clutch performance.
- ◆ Superior resistance to oil thickening
- ◆ Excellent protection against wear

Technical Data*	
SAE Grade	20W-40
Density @ 29.5 oC, g/ml	0.873
Kinematic Viscosity mm ² /s @ 40°C	131
Kinematic Viscosity mm ² /s @ 100°C	14.8
Viscosity Index	115
Flash Point COC	240
Pour Point, °C	-27
TBN, mg KOH/g	7.3
Product Code	220036

*The information prepared provides the typical properties that are considered as representative. Some variation which will not affect performance is possible

HEALTH AND SAFETY, ENVIRONMENT

The information on this product is available in the ENOC Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information, we recommend you review the MSDS. Handled correctly there are no special precautions suggested.