

# ENOC PROTEC 4T X-TREME SN

## PRODUCT DESCRIPTION

ENOC PROTEC 4T X-TREME SN is a high technology fully synthetic lubricant for the latest model gasoline engine oil requiring performance specification exceeding API SM Developed to provide maximum protection in new 4 stroke air cooled motor cycles including low emission engines and for all vehicles. It is available in SAE 5W-40 viscosity grade to provide maximum fuel saving and to meet long drain requirements. Compatible for all motor cycles running on lead free gasoline.

### APPLICATIONS

- All new makes of four stroke motor cycle engines where motor oil is recommended.
- High performance normally aspirated and turbocharged gasoline engines
- Latest model Japanese and European four stroke motor cycle engines.

### PERFORMANCE STANDARDS

PROTEC 4T X-TREME SN meets and exceeds the following International specifications:

API SN JASO MA 2

*Always follow equipment manufacturer's recommendations for required lubricant* performance level and oil drain intervals.

### BENEFITS

### PROTEC 4T X-TREME SN provides:

- The highest level of engine protection for all manufacturers
- Extended engine life
- Superior resistance to oil thickening
- Excellent protection against wear
- Suitable for low emission engines
- Excellent low temperature easy starting
- Superior clutch operation.
- Excellent gear shifting & operation.

Technical Data*	
SAE Grade	5W-40
Density at 15C, kg/L, ASTM D4052	0.8620
Viscosity, Kinematic, ASTM D 445	
mm2/s at 40°C	88.79
mm2/s at 100°C	14.51
Flash Point, °C (COC), ASTM D92	228
Pour Point, °C, ASTM D97	-39
CCS Viscosity, mPa.s, ASTM D 5293	6200@-30°C
Product code	220021

\*The information prepared provides the typical properties that are considered as representative. Some variation which will not affect performance is possible

#### HEALTH AND SAFETY, ENVIRONMENT

The information on this product is available in the ENOC Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information we recommend you review the MSDS. Handled correctly there are no special precautions suggested.

Issued by ENOC Marketing LLC, Dubai, U.A.E Last Updated on: Feb 2020 - ND PDS V2030220