

# ENOC PROTEC HD SF

## PRODUCT DESCRIPTION

**ENOC PROTEC HD SF** is a monograde engine oil developed for gasoline and naturally aspirated diesel engines. It is ideally suited for use in cars and light trucks where the customers' needs can be met with a cost-effective lubricant using standard oil change periods. **PROTEC HD** exceeds the API classification SF and CC

## APPLICATIONS

- ◆ Passenger cars and light commercial vehicles
- ◆ Agriculture tractors
- ◆ Pumps using small gasoline and diesels engines
- ◆ Portable generator sets

## PERFORMANCE STANDARDS

**PROTEC HD SF** meets and exceeds the following International specifications:

API            SF/CC

***Always follow equipment manufacturer's recommendations for required lubricant performance levels and oil drain intervals.***

## BENEFITS

**PROTEC HD SF provides:**

- ◆ Good performance in gasoline and diesel engines
- ◆ Control of sludge and deposits
- ◆ Advanced detergent/dispersant properties
- ◆ Resistance to oil thickening

Technical Data*		
SAE Grade	40	50
Kinematic Viscosity		
mm <sup>2</sup> /s @ 40°C	144	211
mm <sup>2</sup> /s @ 100°C	14.25	18.5
Viscosity Index	96	97
Flash Point, COC, °C	248	260
Pour Point, °C	-15	-9
Product Code	210007	210015

\*The information prepared provides the typical properties that are considered as representative. Some variation which will not affect performance is possible

### HEALTH AND SAFETY, ENVIRONMENT

The information on this product is available in the ENOC Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information we recommend you review the MSDS. Handled correctly there are no special precautions suggested.

Issued by ENOC Marketing LLC, Dubai, U.A.E.  
Last Updated on July 2020- MS  
PDS V2260720