

# **ENOC PROTEC SPEED**

## PRODUCT DESCRIPTION

**ENOC PROTEC SPEED** is a high technology-based gasoline engine oil exceeding the latest API SJ performance specification. Developed to provide maximum protection for use in passenger car. It is suitable for all types of driving conditions (city, highway and harsh). Compatible for all cars running on lead free gasoline and catalytic converters.

### APPLICATIONS

- All makes of passenger cars
- High performance normally aspirated and turbocharged gasoline engines
- Four stroke motorcycle engines where motor oils are recommended
- Japanese and American manufactured cars
- Light commercial vehicles

#### PERFORMANCE STANDARDS

**PROTEC SPEED** meets and exceeds the following International specifications: API SJ, SH ACEA A2/B2

Always follow equipment manufacturer's recommendations for required lubricant performance levels and oil drain intervals.

### BENEFITS

### **PROTEC SPEED provides:**

- Extended Engine Life
- Superior resistance to oil thickening
- Excellent protection against wear
- Low engine deposits
- Easy all year round starting

Technical Data*	
SAE Grade	15W-40
Kinematic Viscosity	
mm²/s @ 40 °C	109
mm²/s @100 °C	14.6
Viscosity Index	138
Flash Point, COC, °C	228
Pour Point, °C	-27
Product Code	210047

\*The information prepared provides the typical properties that are considered as representative. Some variation which will not affect performance is possible

#### HEALTH AND SAFETY, ENVIRONMENT

The information on this product is available in the ENOC Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information, we recommend you review the MSDS. Handled correctly there are no special precautions suggested.

Issued by ENOC Marketing LLC, Dubai, U.A.E. Last Updated on February 2019-ND PDS V2190219