

ENOC PROTEC SUPER SF

PRODUCT DESCRIPTION

ENOC PROTEC SUPER SF is a superior quality multigrade motor oil formulated to meet most American, European and Japanese car manufacturers' specifications. Its formulation is specifically designed for city operations where traffic conditions involve stop - start vehicle patterns as well as general long distance driving.

APPLICATIONS

- All passenger Cars
- Gasoline four stroke engines used in many light duty aplications
- Ideal for multi-trip light vans

PERFORMANCE STANDARDS

PROTEC SUPER SF meets and exceeds the following International specifications:

API SF/CC

Always follow equipment manufacturer's recommendations for required lubricant performance levels and oil drain intervals.

BENEFITS

PROTEC SUPER SF provides:

- Prolonged engine life through excellent wear protection of engine components
- Superior oil consumption control through advanced detergent/dispersant technology
- ♦ Reduced engine deposits, varnish and lacquer
- Suitability for older engines

Technical Data*	
SAE Grade	20W-50
Kinematic Viscosity	
mm ² /s @ 40 ⁰ C	155
mm ² /s @100 ⁰ C	17
Viscosity Index	115
Flash Point, COC, °C	230
Pour Point, ^o C	-24
Product Code	210013

^{*}The information prepared provides the typical properties that are considered as representative. Some variation which will not affect performance is possible

HEALTH AND SAFETY, ENVIRONMENT

The information on this product is available in the ENOC Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information we recommend you review the MSDS. Handled correctly there are no special precautions suggested.

Issued by ENOC Marketing LLC, Dubai, U.A.I

Last Updated on : July 2020-MS

PDS V2260720