

ENOC PROTEC SUPER SG

PRODUCT DESCRIPTION

ENOC PROTEC SUPER is a modern high technology gasoline engine oil, available in a range of viscosity grades which meets the API SG specification for gasoline engines including turbo-charged units. Blended from high quality base oils and advanced additive technology will provide excellent service for modern passenger cars and light commercial vehicles.

APPLICATIONS

- ◆ Passenger cars with multivalve engines with or without turbocharging
- ◆ Japanese and American model cars requiring API SG specification
- ◆ Light commercial trucks with gasoline or light duty diesel engines
- ◆ Motor cycles where four-stroke gasoline engine oils are recommended
- ◆ Portable gasoline engine generator sets

PERFORMANCE STANDARDS

PROTEC SUPER meets and exceeds the following International specifications

API SG

Always follow equipment manufacturer's recommendations for required lubricant performance level and oil drain intervals.

BENEFITS

PROTEC SUPER provides:

- ◆ Long engine life
- ◆ Superior resistance to oil thickening
- ◆ Excellent protection against wear
- ◆ Low engine deposits
- ◆ Easy all year round starting

Technical Data*		
SAE Grade	15W-40	20W-50
Kinematic Viscosity		
mm ² /s @ 40°C	112	166
mm ² /s @ 100°C	15.28	18.5
Viscosity Index	142	125
Flash Point, COC, °C	230	236
Pour Point, °C	-27	-34
Product Code	210025	210003

*The information prepared provides the typical properties that are considered as representative. Some variation which will not affect performance is possible

HEALTH AND SAFETY, ENVIRONMENT

The information on this product is available in the ENOC Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information, we recommend you review the MSDS. Handled correctly there are no special precautions suggested.