

ENOC PROTEC X-TREME SPECIAL

SAE 0W-40

PRODUCT DESCRIPTION

ENOC PROTEC X-TREME SPECIAL is a premium technology **fully synthetic lubricant** for the latest model passenger cars requiring performance specification API SN developed to provide maximum protection for all passenger cars, including high performance engines using Gasoline Direct Injection, Supercharger, turbocharger, common rail light duty diesel passenger cars to meet optimum drain requirements.

APPLICATIONS

- ◆ All new makes of passenger cars
- ◆ High performance cars normally aspirated and turbocharged gasoline engines
- ◆ Cars fitted with exhaust catalytic converters to meet low emission requirements
- ◆ Latest model Japanese, Korean, American and European cars.

PERFORMANCE STANDARDS

PROTEC X-TREME SPECIAL meets the following International specifications:

API SN

Always follow equipment manufacturer's recommendations for required lubricant performance level and oil drain intervals.

BENEFITS

PROTEC X-TREME SPECIAL provides:

- ◆ The highest level of engine protection for all manufacturers
- ◆ Extended engine life
- ◆ Superior resistance to oil thickening
- ◆ Excellent protection against wear
- ◆ Suitable for low emission engines
- ◆ Excellent low temperature easy starting

Technical Data*	
SAE Grade	0W-40
Density kg/m ³ @ 15°C	0.841
Kinematic Viscosity mm ² /s @ 40°C	82.9
Kinematic Viscosity mm ² /s @ 100°C	14.1
Viscosity Index	176
Flash Point COC	226
Pour Point, °C	-39
TBN, mg of KOH/g	9.2
Product Code	210057

*The information prepared provides the typical properties that are considered as representative. Some variation which will not affect performance is possible

HEALTH AND SAFETY, ENVIRONMENT

The information on this product is available in the ENOC Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information we recommend you review the MSDS. Handled correctly there are no special precautions suggested.