

ENOC STRATA MSDO

PRODUCT DESCRIPTION

ENOC STRATA MSDO are a range of new generation high performance engine oils for all types of marine medium speed diesel engines operating on high sulphur residual fuels. They have been developed from the latest complex dispersant and detergent technology to provide long lubrication life and enhanced engine performance particularly in low emission engines and those with anti-bore glazing piston designs.

APPLICATIONS

- ◆ A range of high Total Base Number oils for use in Trunk Piston Engines burning variable quality residual fuel with high sulphur content available in the market
- ◆ Provide gear lubrication qualities for reduction gear applications where similar viscosities might be used
- ◆ Suitable for high output turbocharged engines
- ◆ It is recommended that Strata MSDO oils are suitable for centrifuging and/or filtered in accordance with the manufacturer's instructions
- ◆ Suitable for MAN (B&W), KHD DEUTZ, PIELSTICK, NIGATA, MAK, DAIHATSU, MIRLESS BLACKSTONE trunk piston diesel engines (4 Stroke)

PERFORMANCE STANDARDS

Approved for WARTSILA Marine Engines
 Suitable for use in MAN B&W and Sulzer Marine Engines

BENEFITS

STRATA MSDO provides:

- ◆ Suitability for engines using high sulphur residual or distillate fuels
- ◆ Superior resistance to oxidation and oil thickening
- ◆ Effective neutralisation of acidic combustion products
- ◆ Proven detergent/dispersant technology to reduce deposit formation
- ◆ Long engine and oil service life
- ◆ Excellent centrifugal separator operation

Technical Data*					
Product Grade	320	330	340	350	355
SAE Viscosity	30	30	30	30	30
Density @ 15 deg. C, Kg/L	0.9008	0.9033	0.9110	0.9166	0.9197
Kinematic Viscosity, mm ² /s @ 100°C	11.66	11.52	11.39	11.66	11.59
Kinematic Viscosity, mm ² /s @ 40°C	104.3	106.3	102.2	104.3	103.2
Flash Point °C	240	252	250	240	246
Pour Point, °C	-15	-15	-15	-15	-15
Total Base Number, mg KOH/g	20	30	40	50	55
FZG fail stage (A8.3/90)	12	12	12	12	12
Product code	252021	152022	152023	252024	252025

Issued by ENOC Marketing LLC, Dubai, U.A.E.
 Last Updated: January 2021 - MS
 PDS V3030121

ENOC STRATA MSDO

Technical Data*					
Product Grade	420	430	440	445	450
SAE Viscosity	40	40	40	40	40
Density @ 15 deg. C, Kg/L	0.9011	0.9091	0.9141	0.9221	0.9237
Kinematic Viscosity, mm ² /s @ 100°C	14.55	14.55	14.69	14.45	14.61
Kinematic Viscosity, mm ² /s @ 40°C	147	146	145.2	142.5	143
Flash Point °C	252	252	254	270	250
Pour Point, °C	-15	-15	-15	-15	-15
Total Base Number, mg KOH/g	20	30	40	45	50
FZG fail stage (A8.3/90)	12	12	12	12	12
Product code	152026	152027	152028	152033	252029

Technical Data*			
Product Grade	455	530	540
SAE Viscosity	40	50	50
Density @ 15 deg. C, Kg/L	0.9226	0.9131	0.9181
Kinematic Viscosity, mm ² /s @ 100°C	14.3	19.18	19.10
Kinematic Viscosity, mm ² /s @ 40°C	141.1	212.6	211.5
Flash Point °C	250	258	258
Pour Point, °C	-15	-9	-9
Total Base Number, mg KOH/g	55	30	40
FZG fail stage (A8.3/90)	12	12	12
Product code	252030	252031	252032

*The information prepared provides the typical properties that are considered as representative. Some variation which will not affect performance is possible

HEALTH AND SAFETY, ENVIRONMENT

The information on this product is available in the ENOC Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information we recommend you review the MSDS. Handled correctly there are no special precautions suggested.