

ENOC STRATA SUPER DUTY

PRODUCT DESCRIPTION

STRATA SUPER DUTY 40 is a monograde diesel engine oil developed for the lubrication of for the highest output diesel engines, it is formulated to give better engine protection and longer drain intervals special for marine fast vessels and generators.

APPLICATIONS

- Marine engines used offshore service support vessels
- Construction and heavy earthmoving equipment
- Agriculture tractors

PERFORMANCE STANDARDS

STRATA SUPER DUTY 40 meets and exceeds the International specifications:

API CF

Approved MTU (Type 2)

Always follow equipment manufacturer's recommendations for required lubricant performance levels and oil drain intervals.

BENEFITS

STRATA SUPER DUTY 40 provides:

- ◆ An economical product with good all-round performance
- ◆ Suitability for use in light turbocharging
- ◆ Excellent resistance to oxidation
- ◆ Good engine cleanliness with special detergent/dispersant properties
- ◆ Good resistance to corrosion

Technical Data*	
SAE Grade	40
Density @ 15°C, g/mL	0.8961
Kinematic Viscosity mm ² /s @ 40°C	139
Kinematic Viscosity mm ² /s @100°C	14.75
Viscosity Index	106
Flash Point, COC, °C	242
Pour Point, °C	-30
TBN. ASTM D2896	10.5
Product Code	152036

*The information prepared provides the typical properties that are considered as representative. Some variation which will not affect performance is possible

HEALTH AND SAFETY, ENVIRONMENT

The information on this product is available in the ENOC Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information we recommend you review the MSDS. Handled correctly there are no special precautions suggested.