

# ENOC ULTRA BRAKE FLUID

## PRODUCT DESCRIPTION

**ENOC ULTRA BRAKE FLUID** is a high quality synthetic brake and clutch fluid conforming to the DOT4 specification and based on polyglycol type fluid that is a high-performance standard used in worldwide automotive brake equipment

## APPLICATIONS

- ◆ Suitable for passenger cars, trucks and buses that require DOT 4 synthetic brake fluid
- ◆ High performance cars

## PERFORMANCE STANDARDS

**ULTRA BRAKE FLUID** meets and exceeds the following OEM and International Specifications:

FMVSS 116 DOT 4  
SAE J-1704  
ISO 4925  
NFR 12640

***Always follow equipment manufacturer's recommendations for required lubricant performance levels and oil drain intervals.***

## BENEFITS

**ULTRA BRAKE FLUID provides:**

- ◆ Very High wet boiling point
- ◆ Excellent low temperature stability
- ◆ High temperature viscosity performance
- ◆ Excellent corrosion protection
- ◆ Compatibility with different rubber seals
- ◆ Excellent thermal stability in high performance braking conditions

Technical Data*	
Density g/cm <sup>3</sup>	1.067
Wet Boiling Point, °C min	155
Dry Boiling Point, °C min	230
Viscosity	
mm <sup>2</sup> /s @ -40°C	1500
mm <sup>2</sup> /s @ 100°C	1.5
Product Code	223002

The information prepared provides the typical properties that are considered as representative. Some variation which will not affect performance is possible

**HEALTH AND SAFETY, ENVIRONMENT** The information on this product is available in the ENOC Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information, we recommend you review the MSDS. Handled correctly there are no special precautions suggested.