

# ENOC VULCAN 880 GX SAE 15W-40

## PRODUCT DESCRIPTION

**ENOC VULCAN 880 GX SAE 15W-40** is an advanced heavy-duty diesel engine recommended for modern naturally aspirated and turbocharged four-stroke diesel engine using low or high sulphur fuel in which the API CJ-4 and SAE 15W-40 viscosity grade are recommended. ENOC Vulcan 880 GX SAE 15W-40 is fully backward compatible; thus, enabling use in older generation diesel engines. It is also compatible with modern low emission diesel engines fitted with Selective Catalytic Reduction (SCR), Diesel Particulate Filter (DPF) and Exhaust Gas Recirculation (EGR) systems. In markets with high sulphur fuel, oil condition monitoring gives best assurance on proper drain recommendations.

## APPLICATIONS

- ◆ Heavy duty Diesel Vehicles fitted with exhaust after treatment system such as particulate filters, EGR and catalytic converters to meet low emission requirements EURO V & VI
- ◆ Compatible with other engine oils but recommended not to mix to enhance the life of exhaust after treatment devices.
- ◆ Suitable for mixed fleet operation.
- ◆ Recommend for both on-highway and off-highway applications.

## PERFORMANCE STANDARDS

**ENOC VULCAN 880 GX SAE 15W-40** meets the performance requirements of following Industry bodies and OEM standards:

API	CJ-4/CI-4 Plus/SN
ACEA	E7/E9
CAT	ECF-3
VOLVO	VDS 4
ALLISON	TES-439

*Always follow equipment manufacturer's recommendations for required lubricant performance level and oil drain intervals.*

## BENEFITS

**ENOC VULCAN 880 GX SAE 15W-40** provides:

- ◆ Superior resistance to oil thickening/sludge formation, outstanding deposit control and improve engine life
- ◆ Protects Exhaust After Treatment Devices thus suitable for low emission engines
- ◆ Increase the catalyst life because of low phosphorous level.
- ◆ Provide optimum oil drain intervals and low oil consumption.
- ◆ Excellent protection against wear
- ◆ Specially formulated for protection against heavy load applications.

Technical Data*	
<b>SAE Grade</b>	<b>15W 40</b>
Density kg/m <sup>3</sup>	0.877
Kinematic Viscosity mm <sup>2</sup> /s @ 40°C	112
Kinematic Viscosity mm <sup>2</sup> /s @ 100°C	14.5
Viscosity Index	130
TBN mg KOH/g	9.5
Flash Point COC	236
Pour Point	-30
Product Code	200095

\*The information prepared provides the typical properties that are considered as representative. Some variation which will not affect performance is possible

### HEALTH AND SAFETY, ENVIRONMENT

The information on this product is available in the ENOC Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information, we recommend you review the MSDS. Handled correctly there are no special precautions suggested.