

# ENOC VERRON MP GREASE

## PRODUCT DESCRIPTION

**ENOC VERRON MP** is a high quality, lithium grease formulated with high viscosity base oils, suitable for a wide range of applications. It is available in NLGI 2 and 3 consistencies. They are formulated for use in automotive equipment and general lubrication for use in temperatures up to 120°C and where water contamination can be present. The high-quality base oils these greases have good resistance to oxidation and degradation.

## APPLICATIONS

- ◆ General purpose plain and anti-friction applications
- ◆ Centralised grease systems (NLGI 2)
- ◆ General industrial ball and roller bearings

## RECOMMENDATIONS

**VERRON MP** minimises wear under normal bearing load conditions and resists water wash-out,. It is also effective over a wide temperature range and protects against rust and corrosion. Where vehicles are lubricated by centralised grease systems, **VERRON MP** offers excellent pumpability characteristics.

**Always follow equipment manufacturer's recommendation for required grease** performance and re-lubrication periods.

## BENEFITS

### VERRON MP provides:

- ◆ Resistance to water washout
- ◆ Suitability in wide temperature ranges
- ◆ Good pumpability
- ◆ Good mechanism stability
- ◆ Multifunctional use

Technical Data*		
NLGI Grade	2	3
Dropping point, °C	204	204
Penetration, Worked 25°C	285	236
<b>Oil Viscosity:</b>		
mm <sup>2</sup> /s @ 40°C	200	200
mm <sup>2</sup> /s @ 100°C	17.5	17.5
Thickener soap type	Lithium	Lithium
Operating temperature range continuous service °C	-25 to 120	-20 to 120
Texture	Smooth	Smooth
Product Code	224004	224005

\*The information prepared provides the typical properties that are considered as representative. Some variation which will not affect performance is possible

### HEALTH AND SAFETY, ENVIRONMENT

The information on this product is available in the ENOC Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information, we recommend you review the MSDS. Handled correctly there are no special precautions suggested.