

ENOC VERRON TAC

PRODUCT DESCRIPTION

ENOC VERRON TAC is high performance lithium complex greases with extreme pressure properties fortified with 3% Moly to protect shock load operating conditions, developed for offhighway construction equipment bearing lubrication where they can operate at high loads. It have excellent load carrying and anti-wear properties. It contains an effective oxidation and rust inhibitor and have excellent resistance to water wash-out properties that are important performance requirements for offhighway bearing lubrication.

APPLICATIONS

- ◆ Offhighway construction equipment
- ◆ Heavy duty vehicles
- ◆ Excellent high temperature control under severe breaking
- ◆ Suitable for heavily loaded bearings
- ◆ General mobile equipment
- ◆ Effective temperature range -18°C to 163°C

Always follow equipment manufacturer's recommendation for required grease performance and re-lubrication periods.

BENEFITS

VERRON TAC provides:

- ◆ Protects bearings under shock load operations
- ◆ Excellent Resistance to water wash-out
- ◆ Suitability in high temperature applications
- ◆ Good pumpability
- ◆ Good mechanical stability

Technical Data*	
NLGI Grade	2
Dropping point, °C	260
Penetration, Worked @ 25°C	265
Color	Gray
Oil Viscosity	
mm ² /s @ 40°C	350
mm ² /s @ 100°C	24
Timken OK load, kg	25
Operating temperature range °C	-18 to 163
Product Code	224029

*The information prepared provides the typical properties that are considered as representative. Some variation which will not affect performance is possible

HEALTH AND SAFETY, ENVIRONMENT

The information on this product is available in the ENOC Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information we recommend you review the MSDS. Handled correctly there are no special precautions suggested.

Issued by ENOC International Sales, Dubai, U.A.E.
 Last Updated on : January 2017 MS