

# ENOC VULCAN 700X

## PRODUCT DESCRIPTION

**ENOC VULCAN 700X** is a High Performance long drain diesel engine oil meeting API CH-4 standard available in a shear stable viscosity grade. **VULCAN 700X** offers the excellent performance for fleet operators wanting long engine life in modern long haul diesel trucks operating with low emission engine standards meeting Euro 3 and for extended drain periods.

## APPLICATIONS

- ◆ Mixed fleets of automotive diesel truck manufacturers
- ◆ Modern low emission high performance automotive diesel engines - Euro 3
- ◆ All vehicle makes used in long distance transport with extended oil drain capabilities
- ◆ Heavy duty Mobile Plant vehicles
- ◆ Diesel generator sets

## PERFORMANCE STANDARDS

**VULCAN 700X** meets and exceeds the following OEM and International Specifications:

API CH-4/SJ

Always follow equipment manufacturer's recommendations for required lubricant performance levels and oil drain intervals.

## BENEFITS

### **VULCAN 700X provides:**

- ◆ Excellent engine cleanliness through advanced soot handling technology
- ◆ Mixed fleet capabilities
- ◆ Exceptional low engine wear
- ◆ Trouble free operation between long drain service intervals
- ◆ Reduced maintenance capabilities

Technical Data*	
<b>SAE Grade</b>	<b>20W-50</b>
Kinematic Viscosity	
mm <sup>2</sup> /s @ 40°C	162
mm <sup>2</sup> /s @ 100°C	18.5
Viscosity Index	127
Flash Point, COC, °C	254
Pour Point, °C	-27
BN No. ASTM D2896	9.5
Product Code	200051

\*The information prepared provides the typical properties that are considered as representative. Some variation which will not affect performance is possible

### **HEALTH AND SAFETY, ENVIRONMENT**

The information on this product is available in the ENOC Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information we recommend you review the MSDS. Handled correctly there are no special precautions suggested.