

# ENOC VULCAN 760X SYNTECH

## PRODUCT DESCRIPTION

**ENOC VULCAN 760X SYNTECH 10W-40** is a synthetic blend , extra high performance diesel engine oil developed to provide outstanding lubrication to modern high output diesel engines operating in heavy duty severe on and off-highway applications. This lubricant has been manufactured with highest performance base oils which provide excellent low temperature fluidity, high temperature viscosity retention, volatility control and fuel economy improvement. These base oils are enhanced with an advanced performance additive package, which provides a high level of protection to the entire engine components. **VULCAN 760X SYNTECH** is designed to provide long oil drain service intervals in modern diesel engines.

## APPLICATIONS

- ◆ Natural aspirated and turbo-charged diesel powered engines
- ◆ OEM's engines used in long drain, high mileage applications
- ◆ All vehicle makes used in mixed vehicle transport with extended oil drain capabilities
- ◆ Off-highway industries including; construction, mining, quarrying and agriculture
- ◆ Diesel generator sets

## PERFORMANCE STANDARDS

**VULCAN 760X SYNTECH** meets and exceeds the following OEM and International Specifications:

API	CI-4	Volvo	VDS-3
ACEA	E4/E7	MTU	Type 3.0
MB- Approval	228.5	Renault	RVI RLD-2
MAN	M3277	Cummins CES	20078

Always follow equipment manufacturer's recommendations for required lubricant performance levels and oil drain intervals.

## BENEFITS

**VULCAN 760X SYNTECH provides:**

- ◆ Excellent engine cleanliness through advanced soot handling technology
- ◆ Suitable for Diesel engine in Heavy Equipments, Trucks, Buses and Passenger cars.
- ◆ Exceptional low engine wear
- ◆ Trouble free operation between long drain service intervals
- ◆ Reduced maintenance capabilities
- ◆ Easy starting due to its high fluidity

Technical Data*	
SAE Grade	<b>10W-40</b>
Density at 15°C	0.873
Kinematic Viscosity mm <sup>2</sup> /s @ 40°C	92.58
Kinematic Viscosity mm <sup>2</sup> /s @ 100°C	14.10
Viscosity Index	154
Flash Point, COC, °C	228
Pour Point, °C	-33
BN No. ASTM D2896	12.5
Product Code	200041

\*The information prepared provides the typical properties that are considered as representative. Some variation which will not affect performance is possible

## HEALTH AND SAFETY, ENVIRONMENT

The information on this product is available in the ENOC Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information we recommend you review the MSDS. Handled correctly there are no special precautions suggested