

# ENOC VULCAN KAMUNYE PLUS

## PRODUCT DESCRIPTION

**ENOC VULCAN KAMUNYE PLUS** is a high viscosity monograde engine oil developed for the lubrication of heavy loaded vehicles used in general transport. Especially, heavy jammed traffic that have a lot of start/stop and long idling operation It is designed specifically for use in naturally aspirated and light turbocharged diesel engines. They are formulated to have excellent base number retention, heat removal and protecting the engine over an extended periods of drain intervals.

## APPLICATIONS:

- Vehicles in general transport.
- Construction and heavy earthmoving equipment.
- Light trucks with diesel or gasoline engines.
- Older model passenger cars.
- Certain transmissions requirements for earthmoving equipment.

## PERFORMANCE STANDARDS:

**VULCAN KAMUNYE PLUS** meets and exceeds the following OEM and International specifications:

API

CF/ SF

Always follow equipment manufacturer's recommendations for required lubricant performance levels and oil drain intervals.

## BENEFITS

### VULCAN KAMUNYE PLUS provides:

- ◆ High viscosity that provide good sealing protection
- ◆ Protection for engine in heavy traffic long idling & start/stop operation.
- ◆ Better base number retention.
- ◆ Excellent resistance to oxidation.
- ◆ Good engine cleanliness with special detergent/dispersant properties.
- ◆ Good heat transfer for better engine cooling.

Technical Data*	
<b>SAE Grade</b>	<b>50</b>
Kinematic Viscosity	
mm <sup>2</sup> /s @ 40°C	250
mm <sup>2</sup> /s @ 100°C	21
Viscosity Index	97
Flash Point, COC, °C	260
Pour Point, °C	-14
BN No. ASTM D2896	11
Sulphated Ash %m	1.44
Product Code	200082

## HEALTH AND SAFETY, ENVIRONMENT

The information on this product is available in the ENOC Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information, we recommend you review the MSDS. Handled correctly there are no special precautions suggested.