



ENOC ZENON PREMIUM PLUS SYN

PRODUCT DESCRIPTION

ENOC ZENON PREMIUM PLUS SYN SAE 75W-85 fluid is a Synthetic based high quality, multigrade gear oil suitable for use in cars, trucks, buses, construction plant equipment. It is blended from high quality synthetic base oils and incorporates balanced, extreme pressure chemical technology to minimise scuffing and scoring of transmission gears operating in high speed and high torque conditions where API GL-4 performance is required.

APPLICATIONS

- ◆ Manual synchromesh transmissions for cars, trucks and buses
- ◆ Spiral-Bevel final drive axles in certain makes of vehicles
- ◆ Automotive steering boxes
- ◆ Tractor and off-road heavy equipment, transaxles and differentials

PERFORMANCE STANDARDS

ZENON PREMIUM PLUS SYN meets and exceeds the following International specification:

- API GL-4

Always follow equipment manufacturer's recommendations for the required lubricant performance level and oil drain interval.

BENEFITS

ZENON PREMIUM PLUS SYN provides:

- Robust oxidation and corrosion protection
- Strong wear protection for gears and bearings
- Friction durability with different materials
- High levels of shear stability
- Extended oil drain intervals

SAE Grade	75W-85
Kinematic Viscosity	
mm ² /s @ 40°C	72.5
mm ² /s @ 100°C	11.70
Viscosity Index	156
Pour Point, °C	-45
Flash point C	220
Product Code	222017

*The information prepared provides the typical properties that are considered as representative. Some variation which will not affect performance is possible

HEALTH AND SAFETY, ENVIRONMENT

The information on this product is available in the ENOC Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information we recommend you review the MSDS. Handled correctly there are no special precautions suggested.