اینوك enoc

ENOC ZENON PREMIUM PLUS SYN 75W-90

PRODUCT DESCRIPTION

ENOC ZENON PREMIUM PLUS SYN 75W-90 is Synthetic high-quality manual gear oil engineered to meet extended Long drain requirements of various orginal equipment manufacturers. This product is suitable for use in cars, trucks, buses, construction plant equipment where the API GL4 performance is required, It is blended from high quality synthetic base oils and incorporates balanced, extreme pressure chemical technology to minimise scuffing and scoring of transmission gears operating in high speed and high torque conditions. Especially recommended for trucks and coaches equipped with ZF manual gear boxes.

APPLICATIONS

- Manual synchromesh transmissions for cars, trucks and buses
- ♦ Spiral-Bevel final drive axles in certain makes of vehicles
- Automotive steering boxes
- ♠ Tractor and off-road heavy equipment, transaxles and differentials

PERFORMANCE STANDARDS

ZENON PREMIUM PLUS SYN 75W-90 meets and exceeds the following International specifications:

API GL-4

Always follow equipment manufacturer's recommendations for the required lubricant performance level and oil drain interval.

BENEFITS

ZENON PREMIUM PLUS SYN 75W-90 provides:

- Robust oxidation and corrosion protection
- Strong wear protection for gears and bearings
- Compatibility with different materials in gearbox
- High levels of shear stability
- Extended oil drain capability reducing overhaul and maintenance downtime
- Exceptional thermal stability and resistance to high temperature oxidation

SAE Grade	75W- 90
Kinematic Viscosity	
mm ² /s @ 40°C	94.6
mm ² /s @100°C	14.6
Viscosity Index	162
Pour Point, °C	-51
Flash point C	200
Product Code	222016

^{*}The information prepared provides the typical properties that are considered as representative. Some variation which will not affect performance is possible

HEALTH AND SAFETY, ENVIRONMENT The information on this product is available in the ENOC Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information, we recommend you review the MSDS. Handled correctly there are no special precautions suggested.

Issued by ENOC Marketing LLC, Dubai, U.A.E. Last Updated on: March 2018 – ND PDS V1310319

^{*}Before changing the product, OEM (Original Equipment Manufacturer) guide should be checked, oil changes shall be carried out in accordance with the OEM recommendation.