

ENOC ZENON ULTRA PLUS

PRODUCT DESCRIPTION

ENOC ZENON ULTRA PLUS fluids are superior quality multigrade gear and transmission oils suitable for cars, trucks, construction plants and other mobile equipment. They provide long life by offering a high degree of resistance to gear wear and scuffing. Non scheduled maintenance work can be reduced due to the minimizing of premature gear failures and deposit formation on bearings, working surfaces, and seals which can lead to leakage. They contain balanced extreme pressure chemical technology designed to minimize scuffing and scoring of gear surfaces despite the high speed, high torque, and shock operation.

APPLICATIONS

- ◆ Suitable for heavy-duty service in hypoid, spiral level, spur, and double reduction rear axles
- ◆ Manual gearboxes (constant or synchromesh), auxiliary gearboxes, and transfer boxes.
- ◆ Multi-viscosity gear oils operating conditions over wide temperature ranges
- ◆ Steering boxes and oil-lubricated universal joints.

PERFORMANCE STANDARDS

ZENON ULTRA PLUS meets the following OEM and International specifications:

| | |
|-------------|--|
| API | GL-5 |
| US Military | MIL-L-2105D (for 80W-90 & 85W-140 viscosity grades) |
| MAN | 342 Type M1 & M2 |
| ZF | TE-ML 05A,07A, 12E, 16B, 16C, 16D, 17B, 19B, and 21A |

Always follow equipment manufacturer's recommendations for the required lubricant the performance level and oil drain interval.

BENEFITS

ZENON ULTRA PLUS provides:

- ◆ The opportunity to rationalize gear and transmission oils
- ◆ High load-carrying capacity
- ◆ Superior oxidation resistance
- ◆ Long service life
- ◆ Excellent low-temperature performance
- ◆ Wide temperature of operation

| Technical Data* | | | |
|----------------------------|--------|--------|---------|
| SAE Grade | 80W-90 | 85W 90 | 85W-140 |
| Kinematic Viscosity | | | |
| mm ² /s @ 40°C | 136.6 | 162.10 | 454.7 |
| mm ² /s @ 100°C | 14 | 15.84 | 30.91 |
| Viscosity Index | 99 | 100 | 98 |
| Pour Point, °C | -27 | - 21 | -15 |
| Flash Point | 218 | 224 | 238 |
| Product Code | 222007 | 222019 | 222008 |

*The information prepared provides the typical properties that are considered as representative. Some variation which will not affect performance is possible

HEALTH AND SAFETY, ENVIRONMENT

The information on this product is available in the ENOC Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information we recommend you review the MSDS. Handled correctly there are no special precautions suggested.

Issued by ENOC International Sales, Dubai, U.A.E.
 Last Updated on July 2020- MS
 PDS V2150720