

# ENOC VULCAN 700X ULTRA

## PRODUCT DESCRIPTION

**ENOC VULCAN 700X ULTRA** is a diesel engine oil meeting API CH-4 standard available in a shear stable viscosity grade. **VULCAN 700X ULTRA** offers the excellent performance for fleet operators wanting long engine life in long haul diesel trucks operating with engines standards meeting Euro II & Euro III and for extended drain periods.

## APPLICATIONS

- ◆ Mixed fleets of automotive diesel truck manufacturers
- ◆ Modern low emission high performance automotive diesel engines - Euro II & Euro III
- ◆ All vehicle makes used in long distance transport with extended oil drain capabilities
- ◆ Heavy duty Mobile Plant vehicles
- ◆ Diesel generator sets

## PERFORMANCE STANDARDS

**VULCAN 700X ULTRA** meets and exceeds the following OEM and International Specifications:  
 API CH-4

Always follow equipment manufacturer's recommendations for required lubricant performance levels and oil drain intervals.

## BENEFITS

**VULCAN 700X ULTRA provides:**

- ◆ Excellent engine cleanliness through advanced soot handling technology
- ◆ Mixed fleet capabilities
- ◆ Exceptional low engine wear
- ◆ Trouble free operation between long drain service intervals
- ◆ Reduced maintenance capabilities

Technical Data*		
SAE Grade	15W-40	20W-50
Kinematic Viscosity		
mm <sup>2</sup> /s @ 40°C	107	162
mm <sup>2</sup> /s @ 100°C	14.5	18.5
Viscosity Index	139	127
Flash Point, COC, °C	230	254
Pour Point, °C	-30	-27
BN No. ASTM D2896	9.5	9.5
Product Code	200071	200072

\*The information prepared provides the typical properties that are considered as representative. Some variation which will not affect performance is possible

## HEALTH AND SAFETY, ENVIRONMENT

The information on this product is available in the ENOC Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information we recommend you review the MSDS. Handled correctly there are no special precautions suggested.