

VULCAN SUPER DUTY CD

PRODUCT DESCRIPTION

ENOC VULCAN SUPER DUTY is a range of diesel engine oils developed for the lubrication of heavy goods vehicles used in general transport, earthmoving, quarrying and construction equipment as well as stationary diesel engines requiring API CD quality engine oil. It is designed specifically for use in naturally aspirated and light turbocharged diesel engines. Formulated for moderate to severe service depending on the diesel fuel sulphur level and oil change frequency.

APPLICATIONS

- ◆ Heavy goods vehicles in general transport
- ◆ Construction and heavy earthmoving equipment
- ◆ Engine oils used in mobile air compressors
- ◆ Light trucks with diesel or gasoline engines
- ◆ Older model passenger cars
- ◆ Certain transmissions for earthmoving equipment

PERFORMANCE STANDARDS

VULCAN SUPER DUTY meets and exceeds the following International specifications:

API CD/SE
CCMC D2

Always follow equipment manufacturer's recommendations for required lubricant performance levels and oil drain intervals.

BENEFITS

VULCAN SUPER DUTY provides:

- ◆ An economical product with good all round performance
- ◆ Suitability for use in light turbocharging
- ◆ Excellent resistance to oxidation
- ◆ Good engine cleanliness with special detergent/dispersant properties
- ◆ Good resistance to corrosion

Technical Data*				
SAE Grade	20W- 50	15W – 40	40	50
Kinematic Viscosity				
mm ² /s @ 40°C	167	110.3	142.6	207
mm ² /s @ 100°C	18.6	14.65	14.50	18.5
Viscosity Index	125	136	100	99
Flash Point, COC, °C	242	228	252	264
Pour Point, °C	-24	-30	-15	-9
BN No. ASTM D2896	5.2	5.2	4.7	4.7
Product code	200034	200026	200016	200013

*The information prepared provides the typical properties that are considered as representative. Some variation which will not affect performance is possible

HEALTH AND SAFETY, ENVIRONMENT

The information on this product is available in the ENOC Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information we recommend you review the MSDS. Handled correctly there are no special precautions suggested.