

ENOC ZENON PREMIUM PLUS V

PRODUCT DESCRIPTION

ENOC ZENON PREMIUM PLUS V SAE 75W-90 is fully Synthetic high quality, multigrade gear oil suitable for use in manual transmission of heavy duty trucks. It is blended from high quality synthetic base oils and incorporate balanced, extreme pressure chemical technology to minimise scuffing and scoring of transmission gears operating in high speed and high torque conditions. Especially recommended for use in countries where the ambient temperature is above 30degC.

APPLICATIONS

- ◆ Manual synchromesh transmissions for trucks
- ◆ Developed to meet Volvo 97315 long drain specification

PERFORMANCE STANDARDS

ZENON PREMIUM PLUS V SAE 75W-90 meets and exceeds the following International specifications:

- API GL-4
- Volvo 97315
-

Always follow equipment manufacturer's recommendations for the required lubricant performance level and oil drain interval.

BENEFITS

ZENON PREMIUM PLUS V SAE 75W-90 provides:

- Robust oxidation and corrosion protection
- Strong wear protection for gears and bearings
- Friction durability with different materials
- High levels of shear stability
- Extended oil drain intervals

SAE Grade	75W- 90
Kinematic Viscosity	
mm ² /s @ 40°C	140.0
mm ² /s @100°C	18.25
Viscosity Index	146
Pour Point, °C	-39
Flash point C	235
Product Code	222028

*The information prepared provides the typical properties and does not constitute a specification.

Issued by ENOC CIS-Lubricants, Dubai, U.A.E.
 Last Updated on : December 2019- PB

HEALTH AND SAFETY, ENVIRONMENT

The information on this product is available in the ENOC Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information we recommend you review the MSDS. Handled correctly there are no special precautions suggested.